



## LABEL PRINTER DATAMAX

Robust and space saving



VS7025  
NYA HAMNKROGEN  
12836 5503381  
2023-08-24 425 Hjo/Skvede/Falkping/Mulls

VS7025  
NYA HAMNKROGEN  
12836 5503381  
2023-08-24 425 Hjo/Skvede/Falkping/Mulls

VS7024  
MONS BÅTHUSET  
81785 5503354  
2023-08-24 452 SDERKPING

VS7024  
MONS BÅTHUSET  
81785 5503354  
2023-08-24 452 SDERKPING

# Datamax Label Printer

A durable and robust label printer that prints labels for acknowledging components, storage locations, and orders. Datamax is easily connected to your computer via USB and is up and running in just a few seconds via plug-and-play. The accompanying LabelPoint software gives you a simple gateway to creating custom labels or make use of a library of pre-formed templates.

The printer is designed to be used in places where space is at a premium. No cover needs to be opened when changing labels, you simply load them in through the side of the printer. Datamax uses direct thermal technology, which means that no ink/transfer ribbon is required.



## Item no. FEP01

Supplied complete with a roll of labels 90\*40, network cable, serial cable, and USB cable.

## SPECIFICATION

### General

Manufacturer	Honeywell
Brand	Datamax-O'Neil
Model	Compact 4 Mark III
Colour category	Grey
Pack quantity	1
Compatibility	PC

### Printer

Type	Label printer, printer
Printing technology	Direct thermal
Print type	Monochrome
Max. resolution (black/white)	200 dpi
Max. print speed (black/white)	125 mm/s
Print speed	Up to 125 mm/sec - max. speed
Characteristics	Tear-off
Installed RAM	64 MB
Installed flash memory	128 MB
Firmware	DPL, ZPL

### Media characteristics

Max. media size	Roll (11.5 cm)
Media sizes	Roll (4 - 11.5 cm)
Min. horizontal document size	40 mm
Min. vertical document size	10 mm
Max. horiz. document size	115 mm
Max. printing width	115 mm
Media type	Continuous roll paper labels Matrix printed labels, Z-fold labels
Max. outer diameter of roll	100 mm

### Media characteristics (cont.)

Roll sleeve diameter	40 mm
Media feed	1 x manual - roll - Roll (11.5 cm)
Media thicknesses	0.058 mm - 0.18 mm

### PC connection

Connection technology	Cable connection
PC connection	LAN, Serial, USB
Type	Print server

### Requisite interface

Connectivity	1 x LAN - RJ-45, 1 x RS-232 - 9 pin D-Sub (DB-9), 1 x USB
--------------	---

### Mains connection

Type	Mains unit
Rated voltage	AC 120/230 V
Required frequency	50/60 Hz

### Environmental parameters

Min. operating temperature	5 °C
Max. operating temperature	40 °C
Humidity during operation	10 - 95 % (non-condensing)

### Dimensions and weight

Width	23 cm
Depth	26 cm
Height	10.5 cm
Weight	3.5 kg

### Service and support

Type	1-year warranty
------	-----------------