

LABEL PRINTER
ZEBRA

User-friendly and fast



47
894333
4024072



DB SCHENKER Parcel

46
894331
4024071



DB SCHENKER Parcel

45
894328
4024070



DB SCHENKER Parcel

44
894082
4024066



DB SCHENKER Parcel

Zebra Label Printer

A user-friendly, fast, and value for money printer that prints labels for acknowledging components, storage locations, and orders. Zebra can be easily connected to your computer via USB, or wirelessly using Bluetooth Low Energy.

The Zebra Print DNA software helps create various types of label and tag, easily and without fuss. The printer uses direct thermal technology, which means that no ink/transfer ribbon is required. Printer settings are easy to configure via the mobile app.



Item no. FEP02

The Zebra pack includes 2 centre adapters, 2 supply spindles, a roll of labels 90*40, network cable, serial cable, USB cable, and a mobile app to configure the printer via Bluetooth.

SPECIFICATION

General

Manufacturer	Zebra Technologies
Brand	Zebra
Model	ZD4A042-D0EE00EZ
Colour category	Grey
Pack quantity	1
Compatibility	PC

Printer

Type	Label printer, printer
Printing technology	Direct thermal
Print type	Monochrome
Max. resolution (black/white)	203 dpi
Print speed	Up to 152 mm/sec - max. speed
Functions	Real time clock
Installed RAM (max.)	256 MB
Flash memory	512 MB
Firmware	ZPL II, EPL2, ZBI, Extensible Mark-Up Language (XML), PDF Direct
Internal fonts	16 x bitmapped ZPL II 2 x scalable ZPL 5 x expandable EPL2
Barcode symbologies	Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, LOGMARS, UPC-A, UPC-E, MicroPDF417, Codabar, Code 128, Code 11, Interleaved 2 of 5, Postnet, PDF417, Data Matrix, PLANET, Plessey, Standard 2 of 5, EAN-8, EAN-13, MSI
Agency approvals	FCC Class B certified, VCCI, C-Tick, BSMI, EN 61000-3-2, ICES-003, NOM, SABS, EN 61000-3-3, EN55024, EN55022 Class B, FCC Part 15.247, CCC, IC, IEC 60950-1, KCC, FCC Part 15.209, S Mark, cTUVus, EN 62311, EN 300 328, BIS, INMETRO, CU, RSS-247, IEC 62368-1, EN 301 893, RoHS 2011/65/EU Amendment 2015/863

Media characteristics

Max. media size	Roll (10.8 cm)
Media sizes	Roll (1.5 - 10.8 cm)
Max. media size (standard)	15 mm
Max. media size (custom)	108 mm x 991 mm
Max. printing width	104 mm

Media characteristics (cont.)

Media type	Continuous roll paper labels Matrix printed labels, Z-fold labels
Max. outer diameter of roll	127 mm
Roll sleeve diameter	25.4 mm, 76.2 mm, 38.1 mm, 12.7 mm and 50.8 mm
Media feed	1 x manual - 1 roll - Roll 10.8 cm
Media thickness	0.08 mm - 0.19 mm

PC connection

Connection technology	Cable connection, wireless
PC connection	Bluetooth LE, NFC, USB 2.0, USB host

Requisite interface

Connectivity	1 x USB 2.0 - 4-pin USB type B, 1 x USB host - 4-pin USB type A
--------------	--

Power connection

Type	Power adapter
Rated voltage	AC 120/230 V
Required frequency	50/60 Hz

Environmental standards

ENERGY STAR	Yes
-------------	-----

Environmental parameters

Min. operating temperature	4.4 °C
Max. operating temperature	41 °C
Humidity during operation	10 - 90 % (non-condensing)

Dimensions and weight

Width	17.75 cm
Depth	22.08 cm
Height	15.07 cm
Weight	1.35 kg

Service and support

Type	2-year warranty
------	-----------------