



Compact Lift Shutter Door

The Weland Solutions Shutter Door manufactured from three durable laminate hatches that quickly fold up and down like a roll-up curtain. It dampens any sound produced by the lift machine, keeps products free from dust, and gives the machine a neater appearance. Your stock is fully protected from unauthorized access. The Shutter Door is opened and closed automatically between pick cycles and is located inside the safety curtain. Therefore, when the lift is in motion all moveable parts and personnel are fully protected.

Shutter Doors can be purchased as accessories for new or existing standard height Compact Lift models with tray widths of 1220 – 4000 mm. Where retrofitting is required we would offer this service by technicians who are fully accredited by Weland Solutions.

- Cleaner warehouse products. The protector closes before the lift moves, preventing dust or dirt from being pulled into the lift's storage area by air draughts.
- Quieter operation. The insulating protection makes for a more pleasant working environment.
- Safer storage. The shutter door can only be opened by authorized operators and provides security for your stock.
- **Aesthetically appealing.** The shutter door is a stable, neat, and appealing door solution made from durable grey laminate.

Please contact us and we will help with the specifications for this upgrade.

TECHNICAL INFORMATION

- Door material: 1.5 mm laminate boards filled with 20 mm cellular plastic
- Door thickness: 23 mm
- Lift widths: from 1220 4000 mm (standard height)
- Door opening: goods height up to 775 mm
- Operation: separate integrated NORD motor, chain-driven shutter
- Opening speed: approx. 4-500 mm/sec, depending on door width
- · Colour: Light grey